

VOLTAGE CONTROLLED CRYSTAL OSCILLATOR UNIT WITH HCMOS OUTPUT IN CERAMIC SEAM SEAL SMD PACKAGE, SIZE 5.0 X 3.2MM WITH 6 PADS.


S6VH5

PRODUCT FEATURES

- VCXO IN SMD PACKAGE SIZE 5.0 X 3.2 X 1.2MM WITH 6 PADS.
- WIDE FREQUENCY RANGE 1 TO 245MHZ.
- FREQUENCY PULLING RANGES ± 80 OR ± 100 PPM MINIMUM.
- LOW JITTER AND PHASE NOISE DESIGNS.

APPLICATIONS

- HIGH SPEED NETWORKING
- WIRELESS REPEATERS
- FIBER CHANNEL, TRANSPONDERS
- AUDIO & VIDEO EQUIPMENT




PRODUCT SPECIFICATIONS

PARAMETER	SYMBOL	PARAMETER VALUES / LIMITS	CONDITIONS / REMARKS
NOMINAL FREQUENCY	F_N	1 ~ 50MHZ / 10 ~ 245MHZ	FUNDAMENTAL OR PLL DESIGN
SUPPLY VOLTAGE RANGE	V_{DD}	1.8V _{DC} / 2.5V _{DC} / 3.3V _{DC} / 5.0V _{DC}	—
SUPPLY CURRENT CONSUMPTION	I_{DD}	<35mA	SEE NOTE 1
OVERALL FREQUENCY STABILITY	$\Delta f/F_N$	± 25 PPM, ± 50 PPM, ± 100 PPM	SEE NOTE 2, OTHERS AVAILABLE
AGING FIRST YEAR	$(\Delta f/F_N)_{Y1}$	± 3 PPM	@+25°C
CONTROL VOLTAGE RANGE	V_C	0~1.8V / 0.2~2.3V / 0.3~3.0V / 0.5~4.5V	@ $V_{DD}=1.8V$ / @ $V_{DD}=2.5V$ / @ $V_{DD}=3.3V$ / @ $V_{DD}=5V$
FREQUENCY PULLING RANGE	$\Delta f/V_C$	± 80 PPM / ± 100 PPM	MIN FOR FUNDAMENTAL / PLL DESIGN
OPERATING TEMPERATURE RANGE	T_{OP}	-10°C ~ +70°C / -40°C ~ +85°C	TYPICALLY USED, OTHERS REQUEST
OUTPUT WAVEFORM / LOAD	— / C_L	HCMOS & LVCMOS / 15PF	@ HIGHER SUPPLY VOLTAGES HIGHER LOADS
OUTPUT VOLTAGE LEVELS	V_{OH}/V_{OL}	$\geq 90\%V_{DD}$ / $\leq 10\%V_{DD}$	—
RISE AND FALL TIMES	t_R AND t_F	1 ~ 6ns	@20%~80% OF WAVEFORM
OUTPUT SYMMETRY (DUTY CYCLE)	DC	50 \pm 10% OR 50 \pm 5%	@50% V_{DD}
PHASE JITTER (12KHZ \leq F \leq 20MHZ)	J_{RMS}	1.0ps MAX	FOR 27MHZ
PHASE NOISE (TYPICAL)	$\ell(\Delta f)$	-75 / -104 / -132 / -146 / -148dBc	27MHZ @10Hz,100Hz,1kHz,10kHz,100kHz
STANDBY FUNCTION (E/D ON PIN 2)	E/D	PIN2=HIGH OR OPEN -> OUTPUT PIN4 ACTIVE	PIN2=LOW -> OUTPUT PIN4 HIGH IMPED.

NOTE 1: CURRENT CONSUMPTION IS TYPICAL FOR 3.3V, AT LOWER SUPPLY VOLTAGES LESS CONSUMPTION APPLIES., PLL DESIGNS REQUIRE SLIGHTLY HIGHER POWER.

NOTE 2: OVERALL FREQUENCY STABILITY INCLUDES TOLERANCE @+25°C, DEVIATIONS OVER OPERATING TEMPERATURE RANGE, DEVIATIONS DUE TO OUTPUT LOAD VARIATIONS AND SUPPLY VOLTAGE FLUCTUATIONS.

MECHANICAL DIMENSIONS




VOLTAGE CONTROLLED CRYSTAL OSCILLATOR UNIT WITH HCMOS OUTPUT IN CERAMIC SEAM SEAL SMD PACKAGE, SIZE 5.0 X 3.2MM WITH 6 PADS.


S6VH5

ENVIRONMENTAL COMPLIANCE INFORMATION

- ROHS 6/6 COMPLIANT (DIRECTIVE 2011/65/EC) AND LEAD-FREE.
- COMPLIANT TO ROHS 2 (DIRECTIVE 2015/863) (ALSO CALLED ROHS10).
- HALOGEN-FREE PER DEFINITION OF IEC 61249-2-21 2003.
- NONE-USE OF SVHCs PER REACH IS CURRENTLY GIVEN, CONTINUOUSLY MONITORED AND UPDATED AS THE COMMISSION ISSUES NEW RELEASES.
- PRODUCT DOES NOT CONTAIN ANY PHTHALATES (PHS).
- PRODUCT DOES NOT CONTAIN PVC (POLYVINYL CHLORIDE).
- PRODUCT DOES NOT CONTAIN PFOS/PFOA NOR BEING SAME USED TO MANUFACTURE THE COMPONENTS OF THIS PRODUCT.




SOLDERING RECOMMENDATIONS



PACKAGING INFORMATION

- PACKAGING IN TAPE & REEL IN COMPLIANCE TO EIA-481.
- QTY PER REEL: 1,000PCS
- REEL DIA A=180MM.
- EMBOSSED CARRIER TAPE WIDTH W = 12MM.
- COMPONENT PITCH P1 = 8MM.



PART NUMBER SYNTAX

PART NUMBER FAMILY (REPRESENTS MODEL WITH HCMOS OUTPUT AND PACKAGE SIZE)

SUPPLY VOLTAGE DESIGNATOR (I.E. 50= 5.0V, 33= 3.3V, 25= 2.5V, 18= 1.8V)

FREQUENCY STABILITY CODE (I.E. A= ±25PPM, B= ±50PPM, C= ±100PPM, D= ±30PPM)

NOMINAL FREQUENCY (IN MHZ WITH AT LEAST THREE DIGITS AFTER DECIMAL POINT)

OPERATING TEMPERATURE RANGE CODE (I.E. M= -10~70°C, W= -40~85°C)

OUTPUT SYMMETRY INDICATOR (N= 50±10%, T= 50±5%)


FREQUENCY PULLING RANGE (VALUE IN PPM I.E. 50= ±50PPM, 100= ±100PPM)

FREQUENCY PULLING MODE (BLANK FOR STANDARD, A= ABSOLUTE PULLING RANGE APR)

PART NUMBER EXTENSION (ONLY FOR NON-STANDARD OR CUSTOMIZED PARTS)

IF THERE IS A LARGE NUMBER OF CODES IN USE THE TABLE ABOVE MAY ONLY SHOW A FEW EXAMPLES.

S6VH533 B50.000 MT50 A -EXT



FOR MORE INFORMATION PLEASE CONTACT US.

HONG KONG:

NAKAGAWA ELECTRONICS LIMITED

+852 2389 9201 sales@nkg.com.hk
+852 2341 0001 www.nkg.com.hk

China Shenzhen office:

深圳中川晶体电子有限公司

+86(0)755 2598 2648 sales_sz@nkg.cn
+86(0)755 2598 2390 www.nkg.com.hk

China Suzhou office:

苏州纳美电子有限公司

+86(0)512 8818 7890 sales_nm@nkg.cn
+86(0)512 8818 7889 www.nkg.com.hk